

## Q8 Ruysdael CL 2

### Application

Special grease for applications where the combination of heavy loads, slow speeds and water washout exclude the use of conventional products.

These conditions exist in heavy industries such as steel and paper mills, cement works etc.

Because of the heavy base oil, this grease is not to be recommended for higher speeds because the internal friction within the lubricant film can cause an undesirable temperature increase.

### Specifications

- DIN 51502 classification: KP2K-20
- ISO 6743 classification: ISO-L-XBCIB2

### Benefits

- Extremely good water resistance
- Long service life
- Rust protection under dynamic and static conditions
- Suitable for heavily loaded, slow running plain-, ball- and roller bearings at normal temperatures (-20°C to +150°C)

### Formulation

- Lithium calcium grease based on a high viscosity mineral oil.

To be able to offer our clients products with constantly better characteristics, Kuwait Petroleum reserves the right, without further notice, to modify the specifications of its products at all times.

KUWAIT PETROLEUM INTERNATIONAL LUBRICANTS - NORTHWEST EUROPE

Technical Service  
00800 786 45 787  
[www.Q8oils.com](http://www.Q8oils.com)

KPRT-U03

## Specifications

Specification	Method	Units	
Soap type	-	-	Lithium calcium
Consistency, NLGI No.	-	-	2
Penetration, Worked, 25 °C,			
150 g, 5 s	D 217		
60 strokes	-	0.1 mm	275
100000 Strokes	-	0.1 mm	305
Dropping Point	D 566	°C	190
Four Ball Test, Weld Load	IP 239	N	6650
SKF Emcor Test	DIN 51802	-	pass
SKF R2F Test A	-		pass
SKF R2F Test B, 120 °C	-		pass
Water Washout Test	D 1264	%	0.2
Kin. Viscosity Base Oil at 40 °C	D 445	mm <sup>2</sup> /s	1000

To be able to offer our clients products with constantly better characteristics, Kuwait Petroleum reserves the right, without further notice, to modify the specifications of its products at all times.

KUWAIT PETROLEUM INTERNATIONAL LUBRICANTS - NORTHWEST EUROPE

Technical Service  
00800 786 45 787  
[www.Q8oils.com](http://www.Q8oils.com)

KPRT-U03